

10/524116 524,116

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 March 2004 (18.03.2004)

PCT

(10) International Publication Number
WO 2004/022977 A1

(51) International Patent Classification⁷: **F04C 29/10**

(21) International Application Number:
PCT/BE2003/000130

(22) International Filing Date: 24 July 2003 (24.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002/0514 3 September 2002 (03.09.2002) BE

(71) Applicant (for all designated States except US): **ATLAS COPCO AIRPOWER, NAAMLOZE VENNOOTSCHAP** [BE/BE]; Boomsesteenweg 957, B-2610 Wilrijk (BE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **MOENS, Erik, Eric, Daniël** [BE/BE]; Ommeloper 15, B-9990 Maldegem (BE).

(74) Agent: **DONNÉ, E.**; Bureau M.F.J. Bockstael nv., Arenbergstraat 13, B-2000 Antwerpen (BE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, SZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU,

[Continued on next page]

(54) Title: SPEED CONTROL FOR COMPRESSORS



(57) Abstract: Improvements to a compressor which consists in that, as soon as the measured outlet temperature (TO) reaches a certain hysteresis upper temperature limit (HMAX), the actual rotational speed of the compressor element is either lowered with a speed jump (DS) when the measured rotational speed is situated in the higher speed range close to the maximum rotational speed (SMAX), or is increased with a speed jump (DS) when the measured rotational speed is situated in the lower speed range close to the minimum rotational speed (SMIN).

WO 2004/022977 A1